

# 1489

---

## Description

This adhesive tape, based on a glass fibre scrim, is coated on both sides with a specialised rubber adhesive. The adhesion has a high tack and good resistance to ageing on EPDM. It is lined with a double-sided siliconised paper .

## Areas of use

Because of its high rip-resistance and low elongation the adhesive tape is appropriate for stabilizing rubber profiles and sealing tapes, especially on EPDM-based profiles. It is not designed for use with plasticised PVC.

---

## Technical data\* (provisional edition)

<b>Carrier</b>	Glass scrim
<b>Liner</b>	both sides siliconised paper, brown
<b>Adhesive</b>	rubber
<b>Adhesive coating</b>	250 g/m <sup>2</sup>
<b>Adhesive power</b> (FINAT-TM 1, on stainless steel, one side covered with 50 microns polyester film)	
1 minute	35 N/25 mm
20 minutes	40 N/25 mm
24 hours	45 N/25 mm
<b>Shear strength</b> (FINAT-TM 8, on stainless steel, one side covered with 50 microns polyester film)	
23 °C	24 hours
70°C	10 minutes
<b>Minimum application temperature</b>	+15°C
<b>Temperature resistance</b>	-40°C to + 100°C
<b>Shelf life</b> (at 20 °C and 50 % relative humidity)	1 year

\* The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information, is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications, customers should independently determine the suitability of this material for their specific purpose, prior to use.

---

06/02